

Lightning HT 2 & 3-Pitching Instructions



Lightning HT 3 pictured

In order to familiarize yourself with your new tent, we recommend you "test pitch" it before embarking on your wilderness adventure. For more helpful tips, go to www.sierradesigns.com/tents.html




Package Includes: Tent Body, Rain Fly, 2 Poles, 4 Guy Cords, 6 J-Stakes, 1 Pole Sack with stake pocket.




Step 1: Find an even piece of ground, stake out your tent and assemble the poles. The long grey poles go over doors, be sure long part of ridge pole is to the center and H clip is down.




Step 2: Insert the pole tip of the grey pole into the tent's Jake's Foot™ attachments at each corner. Insert the ridge pole together at center joint.



Jake's Foot™



Swivel Hub w/H clip



Ball Cap™ with SQ Ring™



Jake's Foot™ Fly Attachment



Step 3: Connect the antenna poles to their corresponding Ball Cap™ Connector located over the gray door. Then, working your way around the tent attach the remaining Ultralight Clips™ and H-Clips™ to the tent poles.



Step 4: Drape fly over tent body. Locate the black SQ Ring™ on the underside of the rain fly and connect them to the Ball Cap™ Assembly located at the ends of the antenna poles. Then, secure the rain fly to the front bar of the Jake's Foot™ attachment, stake out the vestibules and admire your new tent.